High Capacity Safety Fill Adapter



Application: These adapters are intended for use on LP-gas delivery truck hose outlets. Features the Industry's Highest Flow Rate for fast delivery while providing the ability to remove the hose end filler valve in the event that the tank fill valve fails to close. During a tank filler valve failure, the integral check valve prevents loss of product. The ME571 is specifically designed to work in conjunction with the ME800 series of minimal loss hose end valves and will allow normal swivel operation of the hose end valve fill nozzle.

Features:

- Industry's Highest Flow Rates 86 GPM LPG @ 30 PSI pressure differential*
- Short overall profile allows valve to remain inside tank dome
- Floating Internal seat design allows product to swivel freely when installed on hose end valve
- Single piece brass body design for maximum product life
- Scalloped body for comfortable and secure grip

Filler Hose Adapters		
Part No.	Description	Hose Connection
ME571H	1-3/4M x 1-3/4F.Acme High Capacity Hose End Check Adpter	1-3/4" Male Acme
Hose End Valves		
Part No.	Description	Hose Connection
ME800	1-3/4 F. Acme Hose End Valve	Standard
ME800C	1-3/4 F. Acme Hose End Valve with Composite Handle	Standard
ME800G	1-3/4 F. Acme Hose End Valve	Fluted
ME800GC	1-3/4 F. Acme Hose End Valve with Composite Handle	Fluted

* Flow rate based on hose end adapter only - downstream valve or restrictions will reduce flow rates



For Your Local Marshall Excelsior Distributor Call 269-789-6700, Fax 269-781-8340 or E-mail: sales@marshallexcelsior.com www.marshallexcelsior.com

