LOW PRESSURE SINGLE STAGE REGULATORS MEGR-230 SERIES



Application:

The MEGR-230 single-stage regulators are approved for use in small portable applications and outdoor cooking appliances ulitizing low pressure.

Note: Single-stage regulators are not approved for RV use.

Part No.	Description
MEGR-218	Single Stage Regulator - SN FF POL w/ Plastic Handwheel x 3/8" FNPT - 90° Vent
MEGR-230	Single Stage Regulator - 1/4" FNPT Inlet X 3/8" FNPT Outlet
MEGR-230-9	Single Stage Regulator - SN .9 GPM Excess Flow POL Inlet x 3/8" FNPT Outlet
MEGR-230-90	Single Stage Regulator - 1/4" FNPT Inlet X 3/8" FNPT Outlet - 90° Vent
MEGR-230-1618	Single Stage Regulator - Black F. QCC x 3/8" FNPT - 90° Vent
MEGR-230-1326	Single Stage Regulator - Black Female QCC Inlet (100,000 BTU/ H) x 3/8" FNPT Outlet
MEGR-231	Single Stage Regulator - Hardnose FF POL x 3/8" FNPT - 90° Vent

MEGR-230 Specifications:

Type: Single Stage Orifice Diameter: .059 Dia

BTU Capacity: 140,000 BTU (based on 25 PSI inlet @ 9" W.C. delivery pressure)

Max. Inlet Pressure:250 PSIInlet Connection:1/4" FNPTOutlet Connection:3/8" FNPTExterior Finish:Green Wet Coat

Diaphragm: Molded with O-Ring Bonnet / Body Seal

Diaphragm Type: Internal Relief - Spring Loaded

Bonnet / Body Material: Die Cast Aluminum Listings: UL LISTED / UL 144 Mounting Holes: 3-1/2" On Center

