




PowerTorq Rotary Actuators



Features:

- **Stainless Steel** all weather mounting hardware
- Actuator unit field repairable under full tank pressure
- Direct drive design does not apply side load to internal valve stem packing for maximum valve life
- No pinch points for operator safety
- Heavy duty pneumatic actuator with 212°F. eutectic fire protection
- Specifically designed for Fisher® Internal Valves & ESV
- Anodized aluminum actuator body with easy to read open/close indicator
- Easy to assemble and can be oriented to suit installation
- Operating Pressure Limits: Minimum - 25 PSIG
Maximum - 125 PSIG
Recommended - 40-60 PSIG
- Features low temperature seals for use with compressed air, nitrogen, or LPG
- Includes mounting bracket for ME707 Quick Release Valve (not required)

Actuators			
Part No.	Description	Fits MEC	Fits
ME225	PowerTorq Actuator	ME990-10	Fisher® C407
ME226	PowerTorq Actuator	ME990-16, ME990-24, ME990S-3F-24	Fisher® C402, C421, C427, C471, C477
ME227	PowerTorq Actuator	ME990S-3DF & ME990S-3DFM	Fisher® C403-24 & C483-24 Series
ME228	PowerTorq Actuator	ME990-4F	Fisher® N550 Series
ME552	PowerTorq Actuator	ME980-10, ME980-16, ME980-16-2F, ME980-24, ME980-24-3F, ME980-24-4F	Fisher® N550 Series

Accessories	
Part No.	Description
ME707	Quick Release Valve - 3/8" FNPT Inlets and Outlets
ME708	Air Pressure Regulator 0-150 PSI - 1/4" FNPT Inlet & Outlet with Mounting Bracket
ME709	1/4" FNPT x 1/4" MNPT LP Gas and Air Filter - Aluminum

**** All PowerTorq Actuators are supplied with heavy duty DOT approved 1/4" tube inlet quick connect swivel and all necessary hardware for easy installation.****